

### **MATERIAL SAFETY DATA SHEET**

ARTIKAMART MSDS NUMBER: 7592440

309, Basement, Sector 21C, PRODUCT CODE: 245376847

Faridabad, Haryana 121001, INDIA DATE: 20/07/2025

### Identification of the substance or mixture and of the supplier

Trade name: Pigment Violet (Oil Soluble)

CAS No.: 12237-62-6

Relevant identified uses of the substance or mixture: Coloring agent for

personal care & Industrial applications (Candles).

**COMPANY: ART VATIKA INSTITUTE** 

**Contact Person:** Mr. Harsh Aggarwal (For commercial and technical detail) **Head Office:** 309, Basement, Sector 21C, Faridabad, Haryana 121001, INDIA.

E-mail: help@artikamart.com
Website: www.artikamart.com

Telephone: +91 9818304044 and +91 8368527252

**Emergency telephone:** In case of chemical emergency involving transportation

spills, leaks, fires or accidents.



#### 3. HAZARDS IDENTIFICATION

No hazardous effects known

The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC or amendments

#### 4. FIRST AID MEASURES

After Inhalation : Supple fresh air

After Eye Contact : Flush with plenty of pressure water for 15 minutes, occasionally raising

eye lids.

After Skin Contact : Wash skin with mild soap and water.

#### 5. FIRE FIGHTING MEASURES

Suitable extinguishing media : No restriction

Special hazards caused by the material, its combustion products or resultant gases : None Special Personal Protective Equipment : None

#### 6. ACCIDENTAL RELEASE MEASURES

Environmental Protection Conduct : Do not sweep or wash into public stretches of water,

sewers or sites of unknown discharge paths.



After Spillage/Leakage/Gas Leakage : Clean up immediately with wetting or absorbent material

avoiding dusting.

7. HANDLING AND STORAGE

Handling : Usual precautions for nuisance dust should be observed

Protection against fire and explosion : The product is non-flammable

Storage : Storage in roofed places at room temperature keep

containers tightly sealed.

Flammability : Not Applicable

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional notes for design of plants equipment: No farther details, see sec7

#### Components with workplace-related limits to be monitored:

Designation % Type of data Unit Nuisance dust 100 MAK 6 mg/m3 TLV/TWA (USA) 10 mg/m3

#### Personal protection equipment

### Respiratory protection:

An appropriate dust fixer has to be used if a breathable dust liberated.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Violet Powder

Odor : Mild
Melting Point : Relative
Density : 3:3 (ibs gal)
Decomposition : None

Flammability : see 7 handling
Molecular formula : C24H27N3
Molecular Weight : 357.49

Tinting strength : 95-105%1 of the standard

Volatile matter at 105°C : 2.5%max

Soluble matter in water : 1.5% max Oil absorption: ≤45 (g/100g)

Fastness to light : 6
Fastness to heat (°C) : 140

Bleeding resistance water : 4-5 Bleeding resistance linseed oil : 4-5 Bleeding resistance acid : 4-5 Bleeding resistance alkalis : 4-5 Bleeding resistance alkalis : 5



Bleeding resistance ethyl acetate : 3

#### 10. STABILITY AND REACTIVITY

Hazardous decomposition products

No decomposition at proper storage and application conditions

#### 11. TOXICOLOGICAL INFORMATION

Because of experience with product mentioned, there are no recognizable hazards for human beings, if it is correctly used and applied.

#### 12. ECOLOGICAL INFORMATION

Avoid filtration into washer draining or soil.

#### 13. DISPOSAL CONSIDERATIONS

Uses should acquaint themselves with local regulations
Disposal is usually carried out by burying at an approved tip or by incineration by a licensed
Waste material processor; stack gases may need to be sorubbed (see section 5 above)

#### 14. TRANSPORT INFORMATION

No declaration for transport required.

#### 15. REGULATORY INFORMATION

Classified according to the Directives 67/548/EEC, and their variation amendments, and labeled as below:

Warning symbols : None
Warning words : None
Risk Phrases : None
Safety Phrases : None

#### 16. OTHER INFORMATION

Listed in EINECS and TSCA inventories.0

Intended uses: Paints and Inks.

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 0



#### **Label Precautions:**

A void contact with eyes, skin and clothing. A void breathing dust. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

#### Label First Aid:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Ifinhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Ifswallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In all cases, get medical attention.